

PLATINIUM

- ZC-B203



Specification

Item	Unit	Specification
Video Parameter		
V/A Carrier	dB	18±2.0
Input Level	Vp-p	0.6~1.5
Input Impedance	Ω	75
Reflection	dB	30
S/N	dB	60
Color/Light Delay	nS	45
Frequency Response	dB	±1.0
Differential Gain	%	±5 (87.5% modulation depth)
Differential Phase	°	±5 (87.5% modulation depth)
Audio Parameter		
Input Level	dBm	-10~+10
Input Impedance	KΩ	10
S/N	dB	60
Distortion	%	1
Frequency Response	dB	±1.0
A/V Difference	MHz	4.5/5.5/6.0/6.5
RF Parameter		
Frequency Range	MHz	47~550, 470~860
Accuracy	KHz	±5
Output level	dBuV	95
Spurious	dBc	60
Output Reflection	dB	12
Output Impedance	Ω	75
General		
Connect Type		IEC, F female, imperial thread
Power Supply	V	AC110~250
Operating Temperature	°C	0 ~ 45
Storage Temperature	°C	-20 ~ 70
Dimension	mm	440 (L)* 125 (W)*44 (H)
Weight	Kg	2.8



High Way, Twin Towers, Sarba P.O.Box 291-Jounieh, LEBANON
Tel: +961 9 643706 Fax: +961 9 645453
Web: www.fiberwaves.com E-mail: info@fiberwaves.com